

Ratings

Temperature: 0 ~ 70 °C
Voltage: 150 V

Conductor

Gauge: 28 AWG, 0.081 mm²
Material: tinned copper strands
Stranding: $\varnothing 0.05 \times 40$
Resistance at 20 °C: 240 Ω /km

Insulator

Material: HDPE
Color: black, white, red
Outer diameter: $\varnothing 0.7 \pm 0.10$ mm
Nominal thickness: 0.15 mm
Resistance at 20 °C: 1000 M Ω /km

Shield

Type: spiral
Material: tinned copper strands
Strand size: $\varnothing 0.08$ mm
Coverage: 90 % minimum

Outer jacket



Material: TPU, 70 °C
Color: cool gray 1C
Nominal thickness: 0.55 mm
Diameter: $\varnothing 2.8 \pm 0.15$ mm

Filler

Material: kevlar

Tests

Tensile strength: 35.7 kgf
Dielectric test: 1500 V dc for 1 minute without breakdown
Bend test at 200 g, $\pm 90^\circ$, 30 cycles /min: 15,000 cycle minimum



REVISION	DATE	DESCRIPTION
A	3/31/2015	Initial release
A1	6/29/2015	removed conductive coating on insulation
A2	1/13/2016	updated note, corrected tolerances

PREPARED:

NOTES

RoHS and REACH compliant

VERIFIED:

Jacket meets ISO 10993 Biological Compatibility

Phthalate and halogen free

DIMENSIONS ARE IN MILLIMETERS

Function test: no open, no short, no intermittent

TOLERANCES:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

DESCRIPTION:

Wire, 3C TS, 28 AWG, 150V, 70C, 2.8 mm, spiral shield, TPU, white

TENSILITY

20802 Sockeye Place #130
Bend, OR 97701 USA

tel 541.323.3228 fax 541.323.4202
800 877.670.7118 www.tensility.com

SIZE

A

PART NUMBER

30-00456

SCALE: 1:1

SHEET 1 OF 1